



Vehicle model	DAILY 2.3 35 / S12-C12 35 / S14-C14 35-40-50 / S16-C16		DAILY 2.3 35 / S12-C12 35 / S14-C14 35-40-50 / S16-C16		DAILY 2.3 35 / S12-C12 35 / S14-C14 35-40-50 / S16-C16		DAILY 2.3 35 / S12-C12 35 / S14-C14 35-40-50 / S16-C16		DAILY 2.3 35 / S12-C12 35 / S14-C14 35-40-50 / S16-C16	
Year	(09/2021>)		(09/2021>)		(09/2021>)		(09/2021>)		(09/2019>)	
Engine Type	F1AGL411 (Euro 6d-full / Euro VI-E)		F1AGL411 (Euro 6d-full / Euro VI-E)		F1AGL411 (Euro 6d-full / Euro VI-E)		F1AGL411 (Euro 6d-full / Euro VI-E)		F1AGL411X (Euro 6d-temp) F1AGL411Y (Euro 6d-temp) F1AGL411W (Euro 6d-temp) F1AGL411U (Euro 6d-temp)	
CV(kW) @ rpm	116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600		116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600		116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600		116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600		116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600	
N. of cylinders/cm3	4 / 2.287		4 / 2.287		4 / 2.287		4 / 2.287		4 / 2.287	
Volts	12		12		12		12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Only Vehicles without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge
										
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 150 / 170 SD7H15 / SD7L15		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 150 / 170 SD7H15 / SD7L15		TM21 / QP21		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 150 / 170 SD7H15 / SD7L15		TM21 / QP21	
Comments	- Kit suitable for both oversized and small oil sump - "E"=TM / QUE / UNICLA; "S"=SANDEN (only for SD7H15 / SD7L15) - Vehicles equipped with QTOR bar - Buy manifold P/N 1170000465 - UNICLA: Clutch drive plate Ø120 not suitable. - Can be fit on AWD vehicles - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 3.0l engine - (*) Vehicles with Hi-Matic 8-speed automatic gearbox manufactured between October 2021 and February 2022, refer to Service Bulletin SB22050057 - In case of Euro 4, 5, 5b+, ask for part number (Not included) P/N 1128000465 - (Recommended) A/C belt mounting tool not included in kit P/N 1161000465 url=https://www.olivatorras.com/kits/info_eines.php?id_prod=20406&type=eines#/urlFor more information#/mask		- (*) High Performance Kit, refer to Service Bulletin SB23100063 - Vehicles equipped with QTOR bar - Buy manifold P/N 1170000465 - Can be fit on AWD vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - (Recommended) A/C belt mounting tool not included in kit P/N 1161000465 url=https://www.olivatorras.com/kits/info_eines.php?id_prod=20406&type=eines#/urlFor more information#/mask		- Kit suitable for both oversized and small oil sump - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 3.0l engine - (*) Vehicles with Hi-Matic 8-speed automatic gearbox manufactured between October 2021 and February 2022, refer to Service Bulletin SB22050057 - (Recommended) A/C belt mounting tool not included in kit P/N 1161000465 url=https://www.olivatorras.com/kits/info_eines.php?id_prod=20406&type=eines#/urlFor more information#/mask		- Kit suitable for both oversized and small oil sump - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - Can be fit on AWD vehicles - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 3.0l engine		- KIT SUITABLE FOR OVERSIZED OIL SUMP IVECO OPTION. Ref. 72617 (SB20100050) - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - Can be fit on AWD vehicles - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 3.0l engine - (Recommended) A/C belt mounting tool not included in kit P/N 1161000465 url=https://www.olivatorras.com/kits/info_eines.php?id_prod=20406&type=eines#/urlFor more information#/mask	
Clutch type	With clutch pulley		With clutch pulley		Without clutch pulley		Without clutch pulley		With clutch pulley	
	1A Ø147 3.380 rpm		Ø126 @ 4460 rpm		1A Ø150 3.312 rpm		2A Ø135 3.386 rpm		1A Ø150 3.312 rpm	
Kit No.	KC18070465E/S		KC23070573E		KC23020563E		KC05100040		KC23020563E	
Last update	2023-07-31		2023-07-27		2023-03-16		2021-09-09		2023-03-16	

Vehicle model	DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG		DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG		DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG	
Year	(09/2021>)		(09/2021>)		(09/2021>)	
Engine Type	F1CFL (Euro 6d-full / Euro VI-E) F1CFA401C (CNG)		F1CFL (Euro 6d-full / Euro VI-E) F1CFA401C (CNG)		F1CFL (Euro 6d-full / Euro VI-E) F1CFA401C (CNG)	
CV(kW) @ rpm	160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500		160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500		160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500	
N. of cylinders/cm3	4 / 2.998		4 / 2.998		4 / 2.998	
Volts	12		12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge
						
Compressors type			TM 13 / 15 / 16 QP 13 / 15 / 16 SD7H15 / SD7L15		UP-UPF 150 / 170	
Comments	(*) High Performance Kit, refer to Service Bulletin SB23100063 - Can be fit in right hand drive vehicles - Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - Kit with two automatic tensioners - Model 35S16 / 35C16 can also be equipped with the 2.3l engine		- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Kit with two automatic tensioners - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 2.3l engine		- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Kit with two automatic tensioners - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 2.3l engine	
Clutch type	Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley	Without clutch pulley	
	Poly-V 8K Ø119 4558 rpm		Poly-V 8K Ø119 3.235 rpm	Poly-V 8K Ø119 3.235 rpm	Poly-V 8K Ø119 3.235 rpm	
Kit No.	KC23100577	KC23100577E	KC15070398	KC15070398E	KC15070398Z	
Last update	2023-10-17		2021-12-13		2021-11-10	

Vehicle model	DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG		DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG		DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG	
Year	(09/2021>)		(09/2021>)		(09/2021>)	
Engine Type	F1CFL (Euro 6d-full / Euro VI-E) F1CFA401C (CNG)		F1CFL (Euro 6d-full / Euro VI-E) F1CFA401C (CNG)		F1CFL (Euro 6d-full / Euro VI-E) F1CFA401C (CNG)	
CV(kW) @ rpm	160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500 (methanol supply)		160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500		160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500	
N. of cylinders/cm3	4 / 2.998		4 / 2.998		4 / 2.998	
Volts	12		12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge
						
Compressors type	TM 21 QP 21		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170		CSA90 / CSA150	
Comments	- "E"=TM / QUE / UNICLA; - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Kit with two automatic tensioners - Recommended fittings 135° - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 2.3l engine		- Can be fit in right hand drive vehicles - Vehicles 136hp, 160hp, 180hp with Hi-Matic 8-speed automatic gearbox, order P/N 1150008086 - On vehicles with Automatic Transmission Hi-Matic, recommended to use crankshaft pulley locking tool P/N 1149000398 - Can't be fit on AWD vehicles - Original accessories belt conserved/modified crossmember bar - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 2.3l engine		- Can be fit in right hand drive vehicles - Vehicles 136hp, 160hp, 180hp with Hi-Matic 8-speed automatic gearbox, order P/N 1150008086 - On vehicles with Automatic Transmission Hi-Matic, recommended to use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Not suitable for front suspension QTOR. - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 2.3l engine	
Clutch type	Without clutch pulley	With clutch pulley	Without clutch pulley		Without clutch pulley	
	Poly-V 8K Ø137 2.810 rpm	Poly-V 8K Ø137 2.810 rpm	Poly-V 8K Ø119 2.941 rpm		1A Ø128 4375 rpm / 1A Ø134 4179 rpm	
Kit No.	KC15070399		KC18090468		KC18100469	
Last update	2021-12-13		2022-07-15		2022-07-15	

Vehicle model	DAILY 2.3 35 / S12-C12 35 / S14-C14 35-40-50 / S16-C16		DAILY 2.3 35 / S12-C12 35 / S14-C14 35-40-50 / S16-C16		DAILY 2.3 35 / S12-C12 35 / S14-C14 35-40-50 / S16-C16		DAILY 2.3 35 / S12-C12 35 / S14-C14 35-40-50 / S16-C16		DAILY 2.3 35 / S12-C12 35 / S14-C14 35-40-50 / S16-C16	
Year	(09/2019>)		(09/2019>)		(09/2019>)		(09/2019>)		(09/2019>)	
Engine Type	F1AGL411 (Euro 6d-full / Euro VI-E)		F1AGL411X (Euro 6d-temp) F1AGL411Y (Euro 6d-temp) F1AGL411W (Euro 6d-temp) F1AGL411U (Euro 6d-temp)		F1AGL411X (Euro 6d-temp) F1AGL411Y (Euro 6d-temp) F1AGL411W (Euro 6d-temp) F1AGL411U (Euro 6d-temp)		F1AGL411X (Euro 6d-temp) F1AGL411Y (Euro 6d-temp) F1AGL411W (Euro 6d-temp) F1AGL411U (Euro 6d-temp)		F1AGL411X (Euro 6d-temp) F1AGL411Y (Euro 6d-temp) F1AGL411W (Euro 6d-temp) F1AGL411U (Euro 6d-temp)	
CV(kW) @ rpm	116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600		116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600		116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600		116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600		116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600	
N. of cylinders/cm3	4 / 2.287		4 / 2.287		4 / 2.287		4 / 2.287		4 / 2.287	
Volts	12		12		12		12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Only Vehicles without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge
										
Compressors type			UP-UPF 150 / 170		TM 13 / 15 / 16 QP 13 / 15 / 16 SD7H15 / SD7L15		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 150 / 170 SD7H15 / SD7L15		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15	
Comments	(*) High Performance Kit, refer to Service Bulletin SB23100063 - Vehicles equipped with QTOR bar - Buy manifold P/N 1170000465 - Can be fit on AWD vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - (Recommended) A/C belt mounting tool not included in kit P/N 1161000465 url=https://www.olivatorras.com/kits/info_eines.php?id_prod=20406&type=eines#urlFor more information#/mask		- KIT NOT SUITABLE FOR OVERSIZED OIL SUMP IVECO OPTION. Ref. 72617 (SB20100050) - UNICLA: Clutch drive plate Ø120 not suitable. - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - Can be fit on AWD vehicles - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 3.0l engine		- KIT NOT SUITABLE FOR OVERSIZED OIL SUMP IVECO OPTION. Ref. 72617 (SB20100050) - "E"=TM / QUE / UNICLA; "S"=SANDEN - "S" only for SD7H15 / SD7L15 - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - Can be fit on AWD vehicles - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 3.0l engine		- KIT SUITABLE FOR OVERSIZED OIL SUMP IVECO OPTION. Ref. 72617 (SB20100050) - "E"=TM / QUE / UNICLA; "S"=SANDEN - "S" only for SD7H15 / SD7L15 - Vehicles equipped with QTOR bar - Buy manifold P/N 1170000465 - UNICLA: Clutch drive plate Ø120 not suitable. - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - Can be fit on AWD vehicles - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 3.0l engine		- KIT SUITABLE FOR OVERSIZED OIL SUMP IVECO OPTION. Ref. 72617 (SB20100050) - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - Can be fit on AWD vehicles - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 3.0l engine	
Clutch type	With clutch pulley		Without clutch pulley		With clutch pulley		3.0l engine with clutch pulley - In case of Euro 4, 5, 5b+, ask for part number (Not included) P/N 1128000465 - (Recommended) A/C belt mounting tool not included in kit P/N 1161000465 url=https://www.olivatorras.com/kits/info_eines.php?id_prod=20406&type=eines#urlFor more information#/mask		Without clutch pulley	
	Ø126 @ 4460 rpm		1A Ø147 3.380 rpm		1A Ø147 3.380 rpm		1A Ø147 3.380 rpm		2A Ø135 3.386 rpm	
Kit No.	KC23070573E		KC15070400Z		KC15070400E/S		KC23070573E		KC05100040	
Last update	2023-07-27		2020-11-30		2019-12-13		2023-07-31		2019-07-29	

Vehicle model	DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG		DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG		DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG	
Year	(09/2019>)		(09/2019>)		(09/2019>)	
Engine Type	F1CFL4116 (Euro 6d-temp) F1CFL4117 (Euro 6d-temp) F1CFL4115 (Euro 6d-temp) F1CFA401C (CNG)		F1CFL4116 (Euro 6d-temp) F1CFL4117 (Euro 6d-temp) F1CFL4115 (Euro 6d-temp) F1CFA401C (CNG)		F1CFL4116 (Euro 6d-temp) F1CFL4117 (Euro 6d-temp) F1CFL4115 (Euro 6d-temp) F1CFA401C (CNG)	
CV(kW) @ rpm	160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500		160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500		160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500 (methanol supply)	
N. of cylinders/cm3	4 / 2.998		4 / 2.998		4 / 2.998	
Volts	12		12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 SD7H15 / SD7L15		UP-UPF 150 / 170		TM 21 QP 21	
Comments	- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Kit with two automatic tensioners - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 2.3l engine		- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Kit with two automatic tensioners - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 2.3l engine		- "E"=TM / QUE / UNICLA; - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Kit with two automatic tensioners - Recommended fittings 135° - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 2.3l engine	
Clutch type	Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley
	Poly-V 8K Ø119 3.235 rpm	Poly-V 8K Ø119 3.235 rpm	Poly-V 8K Ø119 3.235 rpm	With clutch pulley	Poly-V 8K Ø137 2.810 rpm	Poly-V 8K Ø137 2.810 rpm
Kit No.	KC15070398		KC15070398Z		KC15070399	
Last update	2021-09-23		2019-10-03		2019-11-22	

Vehicle model	DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG	DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG	DAILY 2.3 30S12 / 30S14 / 30S16 / 33S12 / 33S14 / 33S16 35S12 / 35S14 / 35S16 / 35C12 / 35C14 / 35C16
Year	(09/2019>)	(09/2019>)	(06/2016-2019)
Engine Type	F1CFL4116 (Euro 6d-temp) F1CFL4117 (Euro 6d-temp) F1CFL4115 (Euro 6d-temp) F1CFA401C (CNG)	F1CFL4116 (Euro 6d-temp) F1CFL4117 (Euro 6d-temp) F1CFL4115 (Euro 6d-temp) F1CFA401C (CNG)	F1AGL411H (Euro 6) F1AGL411J (Euro 6) F1AGL411G (Euro 6)
CV(kW) @ rpm	160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500	160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500 (methanol supply)	116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600
N. of cylinders/cm3	4 / 2.998	4 / 2.998	4 / 2.287
Volts	12	12	12
Air Conditioning	Vehicles with or without A/C	Vehicles with or without A/C	Vehicles with or without A/C
Recommended fittings	Suction	Discharge	Suction
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170	CSA90 / CSA150	UP-UPF 150 / 170
Comments	- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can't be fit on AWD vehicles - Original accessories belt conserved/modified crossmember bar - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 2.3l engine	- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Not suitable for front suspension QTOR. - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 2.3l engine	- UNICLA: Clutch drive plate Ø120 not suitable. - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - Can be fit on AWD vehicles - Model 35S16 / 35C16 can also be equipped with the 3.0l engine
Clutch type	Without clutch pulley	Without clutch pulley	Without clutch pulley
	Poly-V 8K Ø119 2.941 rpm	1A Ø128 4375 rpm / 1A Ø134 4179 rpm	1A Ø147 3.380 rpm
Kit No.	KC18090468	KC18100469	KC15070400Z
Last update	2019-10-08	2019-10-28	2020-11-30


Vehicle model	DAILY 2.3 30S12 / 30S14 / 30S16 / 33S12 / 33S14 / 33S16 35S12 / 35S14 / 35S16 / 35C12 / 35C14 / 35C16	DAILY 2.3 30S12 / 30S14 / 30S16 / 33S12 / 33S14 / 33S16 35S12 / 35S14 / 35S16 / 35C12 / 35C14 / 35C16
Year	(06/2016-2019)	(06/2016>)
Engine Type	F1AGL411H (Euro 6) F1AGL411J (Euro 6) F1AGL411G (Euro 6)	F1AGL411H (Euro 6) F1AGL411J (Euro 6) F1AGL411G (Euro 6)
CV(kW) @ rpm	116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600	116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600
N. of cylinders/cm3	4 / 2.287	4 / 2.287
Volts	12	12
Air Conditioning	Vehicles with or without A/C	Only Vehicles without A/C
Recommended fittings	Suction	Discharge
		
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 SD7H15 / SD7L15	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15
Comments	- "E"=TM / QUE / UNICLA; "S"=SAN DEN - "S" only for SD7H15 / SD7L15 - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - Can be fit on AWD vehicles - Model 35S16 / 35C16 can also be equipped with the 3.0l engine	- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - Can be fit on AWD vehicles - Model 35S16 / 35C16 can also be equipped with the 3.0l engine
Clutch type	With clutch pulley	Without clutch pulley
	1A Ø147 3.380 rpm	2A Ø135 3.386 rpm
Kit No.	KC15070400E/S	KC05100040
Last update	2019-10-13	2019-06-14

Vehicle model	DAILY 3.0 35S15 / 35C15 / 40C15 / 45C15 / 50C15 / 60C15 / 65C15 / 70C15 / 72C15 35S18 / 35C18 / 40C18 / 45C18 / 50C18 / 60C18 / 65C18 / 70C18 / 72C18 35S14 / 35C14 / 40C14 / 50C14 / 60C14 / 65C14 / 70C14 / 72C14 - CNG / NPW		DAILY 3.0 35S15 / 35C15 / 40C15 / 45C15 / 50C15 / 60C15 / 65C15 / 70C15 / 72C15 35S18 / 35C18 / 40C18 / 45C18 / 50C18 / 60C18 / 65C18 / 70C18 / 72C18 35S14 / 35C14 / 40C14 / 50C14 / 60C14 / 65C14 / 70C14 / 72C14 - CNG / NPW	
Year	(09/2014>)		(09/2014>)	
Engine Type	F1CFL411E*A / F1CGL411E*A / F1CGL411A*E (Euro 6) F1CFL411F*A / F1CGL411F*A / F1CGL411B*E (Euro 6) F1CFA401A*A (CNG)		F1CFL411E*A / F1CGL411E*A / F1CGL411A*E (Euro 6) F1CFL411F*A / F1CGL411F*A / F1CGL411B*E (Euro 6) F1CFA401A*A (CNG)	
CV(kW) @ rpm	150 (110) @ 3.500 180 (132) @ 3.500 136 (100) @ 3.500 (methanol supply)		150 (110) @ 3.500 180 (132) @ 3.500 136 (100) @ 3.500 (methanol supply)	
N. of cylinders/cm3	4 / 2.998		4 / 2.998	
Volts	12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge
				
Compressors type			TM 13 / 15 / 16 QP 13 / 15 / 16 SD7H15 / SD7L15	
Comments	- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Kit with two automatic tensioners - Model 35S16 / 35C16 can also be equipped with the 2.3l engine		- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Kit with two automatic tensioners - Model 35S16 / 35C16 can also be equipped with the 2.3l engine	
Clutch type	Without clutch pulley		Without clutch pulley	With clutch pulley
	Poly-V 8K Ø137 3.690 rpm		Poly-V 8K Ø119 3.235 rpm	Poly-V 8K Ø119 3.235 rpm
Kit No.	KC24010582		KC15070398	KC15070398E
Last update	2021-09-23		2021-09-23	


Vehicle model	DAILY 3.0 35S15 / 35C15 / 40C15 / 45C15 / 50C15 / 60C15 / 65C15 / 70C15 / 72C15 35S18 / 35C18 / 40C18 / 45C18 / 50C18 / 60C18 / 65C18 / 70C18 / 72C18 35S14 / 35C14 / 40C14 / 50C14 / 60C14 / 65C14 / 70C14 / 72C14 - CNG / NPW		DAILY 3.0 35S15 / 35C15 / 40C15 / 45C15 / 50C15 / 60C15 / 65C15 / 70C15 / 72C15 35S18 / 35C18 / 40C18 / 45C18 / 50C18 / 60C18 / 65C18 / 70C18 / 72C18 35S14 / 35C14 / 40C14 / 50C14 / 60C14 / 65C14 / 70C14 / 72C14 - CNG / NPW	
Year	(09/2014>)		(09/2014>)	
Engine Type	F1CFL411E*A / F1CGL411E*A / F1CGL411A*E (Euro 6) F1CFL411F*A / F1CGL411F*A / F1CGL411B*E (Euro 6) F1CFA401A*A (CNG)		F1CFL411E*A / F1CGL411E*A / F1CGL411A*E (Euro 6) F1CFL411F*A / F1CGL411F*A / F1CGL411B*E (Euro 6) F1CFA401A*A (CNG)	
CV(kW) @ rpm	150 (110) @ 3.500 180 (132) @ 3.500 136 (100) @ 3.500 (methanol supply)		150 (110) @ 3.500 180 (132) @ 3.500 136 (100) @ 3.500 (methanol supply)	
N. of cylinders/cm3	4 / 2.998		4 / 2.998	
Volts	12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge
				
Compressors type	UP-UPF 150 / 170		TM 21 QP 21	
Comments	- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Kit with two automatic tensioners - Model 35S16 / 35C16 can also be equipped with the 2.3l engine		- "E"=TM / QUE / UNICLA; - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Kit with two automatic tensioners - Recommended fittings 135°	
Clutch type	Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley
	Poly-V 8K Ø119 3.235 rpm	Poly-V 8K Ø119 3.235 rpm	Poly-V 8K Ø137 2.810 rpm	Poly-V 8K Ø137 2.810 rpm
Kit No.	KC15070398Z	KC15070398ZE	KC15070399	KC15070399E
Last update	2020-03-03		2021-09-27	

Vehicle model	DAILY 3.0 35S15 / 35C15 / 40C15 / 45C15 / 50C15 / 60C15 / 65C15 / 70C15 / 72C15 35S18 / 35C18 / 40C18 / 45C18 / 50C18 / 60C18 / 65C18 / 70C18 / 72C18 35S14 / 35C14 / 40C14 / 50C14 / 60C14 / 65C14 / 70C14 / 72C14 - CNG / NPW	DAILY 3.0 35S15 / 35C15 / 40C15 / 45C15 / 50C15 / 60C15 / 65C15 / 70C15 / 72C15 35S18 / 35C18 / 40C18 / 45C18 / 50C18 / 60C18 / 65C18 / 70C18 / 72C18 35S14 / 35C14 / 40C14 / 50C14 / 60C14 / 65C14 / 70C14 / 72C14 - CNG / NPW
Year	(09/2014>)	(09/2014>)
Engine Type	F1CFL411E*A / F1CGL411E*A / F1CGL411A*E (Euro 6) F1CFL411F*A / F1CGL411F*A / F1CGL411B*E (Euro 6) F1CFA401A*A (CNG)	F1CFL411E*A / F1CGL411E*A / F1CGL411A*E (Euro 6) F1CFL411F*A / F1CGL411F*A / F1CGL411B*E (Euro 6) F1CFA401A*A (CNG)
CV(kW) @ rpm	150 (110) @ 3.500 180 (132) @ 3.500 136 (100) @ 3.500 (methanol supply)	150 (110) @ 3.500 180 (132) @ 3.500 136 (100) @ 3.500 (methanol supply)
N. of cylinders/cm3	4 / 2.998	4 / 2.998
Volts	12	12
Air Conditioning	Vehicles with or without A/C	Vehicles with or without A/C
Recommended fittings	Suction	Discharge
		
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170	CSA90 / CSA150
Comments	- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can't be fit on AWD vehicles - Original accessories belt conserved/modified crossmember bar	- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Not suitable for front suspension QTOR.
Clutch type	Without clutch pulley	Without clutch pulley
	Poly-V 8K Ø119 2.941 rpm	1A Ø128 4375 rpm / 1A Ø134 4179 rpm
Kit No.	KC18090468	KC18100469
Last update	2018-11-09	2018-10-25

Vehicle model	DAILY 3.0 35S21 / 35C21 / 40C21 / 45C21 50C21 / 60C21 / 65C21 / 70C21 / 72C21		DAILY 3.0 35S21 / 35C21 / 40C21 / 45C21 50C21 / 60C21 / 65C21 / 70C21 / 72C21		DAILY 3.0 35S21 / 35C21 / 40C21 / 45C21 50C21 / 60C21 / 65C21 / 70C21 / 72C21	
Year	(09/2014>)		(08/2014>09/2019)		(08/2014>09/2019)	
Engine Type	F1CFL411E*A / F1CGL411E*A / F1CGL411A*E (Euro 6) F1CFL411F*A / F1CGL411F*A / F1CGL411B*E (Euro 6) F1CFA401A*A (CNG)		F1CFL411C*E (Euro 6) / F1CGL411C*E (Euro 6)		F1CFL411C*E (Euro 6) / F1CGL411C*E (Euro 6)	
CV(kW) @ rpm	150 (110) (110) @ 3.500 180 (132)		205 (151) @ 3.500		205 (151) @ 3.500	
N. of cylinders/cm3	4 / 2.998		4 / 2.998		4 / 2.998	
Volts	12		12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge
						
Compressors type			TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14		TM 21 QP 21	
Comments	(*) High Performance Kit, refer to Service Bulletin SB23100063 - Can be fit in right hand drive vehicles - Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - Kit with two automatic tensioners - Model 35S16 / 35C16 can also be equipped with the 2.3l engine		- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398		- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398	
Clutch type	Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley
	Poly-V 8K Ø119 4558 rpm		Poly-V Ø119 3.235 rpm	Poly-V 8K Ø119 3.235 rpm	Poly-V 8K Ø137 2.810 rpm	Poly-V 8K Ø137 2.810 rpm
Kit No.	KC23100577	KC23100577E	KC14080374	KC14080374E	KC14090377	KC14090377E
Last update	2023-10-17		2019-05-09		2016-05-12	

Vehicle model	DAILY 2.3 33S11 / 35S11 / 35C11 33S13 / 35S13 / 35C13 33S15 / 35S15 / 35C15	DAILY 2.3 33S11 / 35S11 / 35C11 33S13 / 35S13 / 35C13 33S15 / 35S15 / 35C15	DAILY 2.3 33S11 / 35S11 / 35C11 33S13 / 35S13 / 35C13 33S15 / 35S15 / 35C15
Year	(08/2014>)	(08/2014>)	(08/2014>)
Engine Type	F1AFL411A*A (Euro 5b+) F1AFL411B*A (Euro 5b+) F1AFL411C*A (Euro 5b+)	F1AFL411A*A (Euro 5b+) F1AFL411B*A (Euro 5b+) F1AFL411C*A (Euro 5b+)	F1AFL411A*A (Euro 5b+) F1AFL411B*A (Euro 5b+) F1AFL411C*A (Euro 5b+)
CV(kW) @ rpm	106 (78) @ 3.900 126 (93) / 146 (107) @ 3.600	106 (78) @ 3.900 126 (93) / 146 (107) @ 3.600	106 (78) @ 3.900 126 (93) / 146 (107) @ 3.600
N. of cylinders/cm3	4 / 2.287	4 / 2.287	4 / 2.287
Volts	12	12	12
Air Conditioning	Vehicles with or without A/C	Vehicles with or without A/C	Only Vehicles without A/C
Recommended fittings	Suction	Discharge	Suction
			 
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 150 / 170 SD7H15 / SD7L15	TM21 / QP21	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15
Comments	- "E"=TM / QUE / UNICLA; "S"=SANDEN - "S" only for SD7H15 / SD7L15 - UNICLA: Clutch drive plate Ø120 not suitable. - Model 35S15 / 35C15 can also be equipped with the 3.0l engineç - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - In case of a Euro 4, 5 o 5b+ vehicle, ask for the reference P/N 1128000465	- Model 35S15 / 35C15 can also be equipped with the 3.0l engineç - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic.	- Can be fit in right hand drive vehicles - Model 35C15 can also be equipped with the 3.0l engine - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic.
Clutch type	With clutch pulley	With clutch pulley	Without clutch pulley
	1A Ø147 3.380 rpm	1A Ø150 3.3312 rpm	2A Ø135 3.386 rpm
Kit No.	KC18070465E/S	KC23020563E	KC05100040
Last update	2023-07-31	2023-03-16	2019-06-13

Vehicle model	DAILY 3.0 35S15 / 35C15 / 50C15 / 65C15 / 70C15 35S17 / 35C17 / 50C17 / 65C17 / 70C17		DAILY 3.0 35S15 / 35C15 / 50C15 / 65C15 / 70C15 35S17 / 35C17 / 50C17 / 65C17 / 70C17		DAILY 3.0 35S21 / 35C21 50C21 / 65C21 / 70C21		DAILY 3.0 35S21 / 35C21 50C21 / 65C21 / 70C21	
Year	(09/2014>)		(09/2014>)		(08/2014>09/2019)		(08/2014>09/2019)	
Engine Type	F1CFL411J*C (Euro 5b+) F1CFL411H*C (Euro 5b+)		F1CFL411J*C (Euro 5b+) F1CFL411H*C (Euro 5b+)		F1CFL411G*C (Euro 5b+)		F1CFL411G*C (Euro 5b+)	
CV(kW) @ rpm	146 (107) @ 3.500 170 (125) @ 3.500		146 (107) @ 3.500 170 (125) @ 3.500		205 (151) @ 3.500		205 (151) @ 3.500	
N. of cylinders/cm3	4 / 2.998		4 / 2.998		4 / 2.998		4 / 2.998	
Volts	12		12		12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge
								
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 SD7H15 / SD7L15		TM 21 QP 21		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14		TM 21 QP 21	
Comments	- Can be fit in right hand drive vehicles - Model 35C15 can also be equipped with the 2.3l engine - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Kit with two automatic tensioners		- "E"=TM / QUE / UNICLA; - Can be fit in right hand drive vehicles - Model 35C15 can also be equipped with the 2.3l engine - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Recommended fittings 135°		- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398		- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398	
Clutch type	Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley
	Poly-V 8K Ø119 3.235 rpm	Poly-V 8K Ø119 3.235 rpm	Poly-V 8K Ø137 2.810 rpm	Poly-V 8K Ø137 2.810 rpm	Poly-V Ø119 3.235 rpm	Poly-V 8K Ø119 3.235 rpm	Poly-V 8K Ø137 2.810 rpm	Poly-V 8K Ø137 2.810 rpm
Kit No.	KC15070398	KC15070398E	KC15070399	KC15070399E	KC14080374	KC14080374E	KC14090377	KC14090377E
Last update	2021-09-23		2019-11-22		2015-03-25		2019-05-09	

Vehicle model	DAILY 2.3 29L11 / 35S11 / 35C11 / 40C11 29L13 / 35S13 / 35C13 / 40C13 29L15 / 35S15 / 35C15	DAILY 2.3 29L11 / 35S11 / 35C11 / 40C11 29L13 / 35S13 / 35C13 / 40C13 29L15 / 35S15 / 35C15	DAILY 2.3 29L11 / 35S11 / 35C11 / 40C11 29L13 / 35S13 / 35C13 / 40C13 29L15 / 35S15 / 35C15
Year	(11/2011)	(11/2011)	(11/2011)
Engine Type	F1AE3481A (Euro 5) F1AE3481B (Euro 5) F1AE3481C (Euro 5)	F1AE3481A (Euro 5) F1AE3481B (Euro 5) F1AE3481C (Euro 5)	F1AE3481A (Euro 5) F1AE3481B (Euro 5) F1AE3481C (Euro 5)
CV(kW) @ rpm	106 (78) @ 3.900 126 (93) / 146 (107) @ 3.600	106 (78) @ 3.900 126 (93) / 146 (107) @ 3.600	106 (78) @ 3.900 126 (93) / 146 (107) @ 3.600
N. of cylinders/cm3	4 / 2.287	4 / 2.287	4 / 2.287
Volts	12	12	12
Air Conditioning	Vehicles with or without A/C	Vehicles with or without A/C	Only Vehicles without A/C
Recommended fittings	Suction	Discharge	Suction
			
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 150 / 170 SD7H15 / SD7L15	TM21 / QP21	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15
Comments	- "E"=TM / QUE / UNICLA; "S"=SANDEN - "S" only for SD7H15 / SD7L15 - Can be fit in right hand drive vehicles - Model 35C15 can also be equipped with the 3.0l engine - In case of a Euro 4, 5 o 5b+ vehicle, ask for the reference P/N 1128000465	- Can be fit in right hand drive vehicles - Model 35C15 can also be equipped with the 3.0l engine	- Can be fit in right hand drive vehicles - Suitable for vehicles equipped with automatic gear box - Model 35C15 can also be equipped with the 3.0l engine
Clutch type	With clutch pulley	With clutch pulley	Without clutch pulley
	1A Ø147 3.380 rpm	1A Ø147 3.380 rpm	2A Ø135 3.386 rpm
Kit No.	KC18070465E/S	KC23020563E	KC05100040
Last update	2023-07-31	2023-03-16	2019-06-13

Vehicle model	DAILY 3.0 35C15 / 40C15 / 50C15/ 65C15/70C15 35S17 / 35C17 / 40C17 / 50C17 / 65C17 / 70C17		DAILY 3.0 35C15 / 40C15 / 50C15/ 65C15/70C15 35S17 / 35C17 / 40C17 / 50C17 / 65C17 / 70C17		DAILY 3.0 35C15 / 40C15 / 50C15/ 65C15/70C15 35S17 / 35C17 / 40C17 / 50C17 / 65C17 / 70C17	
Year	(11/2011>)		(11/2011>)		(11/2011>)	
Engine Type	F1CE3481J (Euro 5) F1CE3481K (Euro 5)		F1CE3481J (Euro 5) F1CE3481K (Euro 5)		F1CE3481J (Euro 5) F1CE3481K (Euro 5)	
CV(kW) @ rpm	146 (107) @ 3.500 170 (125) @ 3.500		146 (107) @ 3.500 170 (125) @ 3.500		146 (107) @ 3.500 170 (125) @ 3.500	
N. of cylinders/cm3	4 / 2.998		4 / 2.998		4 / 2.998	
Volts	12		12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge
						
Compressors type	TM 21 QP 21		TM 13 / 15 / 16 QP 13 / 15 / 16 SD7H15 / SD7L15		UP-UPF 150 / 170	
Comments	- "E"=TM / QUE / UNICLA; - Can be fit in right hand drive vehicles - Model 35C15 can also be equipped with the 2.3l engine - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - Kit with two automatic tensioners - Recommended fittings 135°		- UNICLA: Clutch drive plate Ø120 not suitable. - Can be fit in right hand drive vehicles - Model 35S15 / 35C15 can also be equipped with the 2.3l engine - Kit with two automatic tensioners		- UNICLA: Clutch drive plate Ø120 not suitable. - Can be fit in right hand drive vehicles - Model 35S15 / 35C15 can also be equipped with the 2.3l engine - Kit with two automatic tensioners	
Clutch type	Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley	Without clutch pulley	
	Poly-V 8K Ø137 2.810 rpm	Poly-V 8K Ø137 2.810 rpm	Poly-V 8K Ø119 3.235 rpm	Poly-V 8K Ø119 3.235 rpm	Poly-V 8K Ø119 3.235 rpm	
Kit No.	KC15070399		KC15070398		KC15070398Z	
Last update	2019-11-22		2021-09-23		2021-12-02	

Vehicle model	DAILY 3.0 35S21 / 35C21 / 40C21 / 50C21 / 65C21 / 70C21		DAILY 3.0 35C14 / 40C14 / 50C14 / 65C14 35S17 / 35C17 / 40C17 / 50C17 / 65C17		DAILY 2.3 29L10 / 35S10 / 35C10 / 40C10 / 29L11 / 35S11 / 35C11 (2.3 HPI) 29L12 / 35S12 / 35C12 / 40C12 (2.3 HPI) 29L13 / 35S13 / 35C13 / 29L14 / 35S14 / 35C14 (2.3 HPT)	
Year	(11/2011>)		(2009>)		(2002>)	
Engine Type	F1CE3481D (Euro 5)		F1CE3481L (EEV) F1CE3481C (EEV)		F1AE0481A-F / F1AE0481B-G (Euro 3-4) F1AE0481M-H (Euro 3-4) F1AE0481U/ F1AE0481V (Euro 4)	
CV(kW) @ rpm	205 (151) @ 3.500		140 (103) @ 3.500 170 (125) @ 3.500		96 (71) @ 3.900 116 (85) @ 3.900 136 (100) @ 3.900 106 (78) @ 3.900	
N. of cylinders/cm3	4 / 2.998		4 / 2.998		4 / 2.287	
Volts	12		12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge
						
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD7H15 / SD7L15		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 150 / 170 SD7H15 / SD7L15	
Comments	- Can be fit in right hand drive vehicles		- "E"=TM / QUE / UNICLA; "S"=SANDEN - "S" only for SD7H15 / SD7L15. - Can be fit in right hand drive vehicles - For compressor TM-08 and UP-90 it is essential to indicate the compressor in the order.		- "E"=TM / QUE / UNICLA; "S"=SANDEN - "S" only for SD7H15 / SD7L15 - Can be fit in right hand drive vehicles - In case of a Euro 4, 5 o 5b+ vehicle, ask for the reference P/N 1128000465	
Clutch type	Without clutch pulley	With clutch pulley	With clutch pulley		With clutch pulley	
	Poly-V Ø119 3.235 rpm	Poly-V 8K Ø119 3.235 rpm	1A Ø150 3.220 rpm		1A Ø147 3.380 rpm	
Kit No.	KC12050272	KC12050272E	KC05100006E/S		KC18070465E/S	
Last update	2015-03-25		2019-06-13		2023-07-31	

Vehicle model	DAILY 2.3 29L10 / 35S10 / 35C10 / 40C10 / 29L11 / 35S11 / 35C11 (2.3 HPI) 29L12 / 35S12 / 35C12 / 40C12 (2.3 HPI) 29L13 / 35S13 / 35C13 / 29L14 / 35S14 / 35C14 (2.3 HPT)		DAILY 2.8 29L09 / 35S09 / 35C09 / 40C09 29L11 / 35S11 / 35C11 / 40C11 / 45C11 / 50C11 35S13 / 35C13 / 40C13 / 45C13 / 50C13 / 65C15	
Year	(2002>)		(2001>)	
Engine Type	F1AE0481A-F / F1AE0481B-G (Euro 3-4) F1AE0481M-H (Euro 3-4) F1AE0481U/ F1AE0481V (Euro 4)		8140.63 (Euro 2) 8140.43 C / S / N (Euro 2)	
CV(kW) @ rpm	96 (71) @ 3.900 116 (85) @ 3.900 136 (100) @ 3.900 106 (78) @ 3.900		85 (62) @ 3.800 105 (77) / 125 (92) / 146 (107) @ 3.600	
N. of cylinders/cm3	4 / 2.287		4 / 2.798	
Volts	12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge
				
Compressors type	TM21 / QP21		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15	
Comments	- Can be fit in right hand drive vehicles		- Can be fit in right hand drive vehicles	
Clutch type	With clutch pulley		Without clutch pulley	
	1A Ø150 3.3312 rpm		2A Ø135 2.510 rpm	
Kit No.	KC23020563E		KC05100005	
Last update	2023-03-16		2013-12-18	

Vehicle model	DAILY 3.0 HPI - HPT 35C14 / 40C14 / 50C14 / 65C14 / 35C15 / 40C15 / 50C15 / 60C15 / 65C15 35S17 / 35C17 / 40C17 / 50C17 / 65C17 / 35S18 / 35C18 / 40C18 / 50C18 / 60C18 / 65C18	EuroCargo Tector 5 ML60E16 / ML65E16 / ML75E16 / ML80EL16 ML75E19 / ML80E19 / ML80EL19 / ML90E19 / ML100E19 / ML110EL19/ ML120EL19 ML75E21 / ML80E21 / ML80EL21 / ML90E21 / ML100E21 / ML110EL21 / ML120EL21
Year	(2004>)	(09/2019<)
Engine Type	F1CE0481A-F (Euro 3-4) F1CE0481B-H (Euro 3-4)	F4AFE411E*N (Euro 6D Temp) F4AFE411F*N (Euro 6D Temp) F4AFE411C*N (Euro 6D Temp)
CV(kW) @ rpm	136 (100) / 146 (107) @ 3.500 166 (122) / 176 (129) @ 3.500	160 (118) @ 2.500 190 (140) @ 2.500 210 (154) @ 2.500
N. of cylinders/cm3	4 / 2.998	4 / 4.485
Volts	12	24
Air Conditioning	Vehicles with or without A/C	Vehicles with or without A/C
Recommended fittings	Suction	Suction
		
Recommended fittings	Discharge	Discharge
		
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD7H15 / SD7L15	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15
Comments	- "E"=TM / QUE / UNICLA; "S"=SANDEN - "S" only for SD7H15 / SD7L15. - Can be fit in right hand drive vehicles - For compressor TM-08 and UP-90 it is essential to indicate the compressor in the order.	- Can't be fit in right hand drive vehicles - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox
Clutch type	With clutch pulley	Without clutch pulley
	1A Ø150 3.220 rpm	2A Ø135 3.520 rpm
Kit No.	KC05100006E/S	KC07040110
Last update	2019-06-13	2020-01-22

Vehicle model	EuroCargo Tector 5 ML60E16 / ML65E16 / ML75E16 / ML80EL16 ML75E19 / ML80E19 / ML80EL19 / ML90E19 / ML100E19 / ML110EL19 / ML120EL19 ML75E21 / ML80E21 / ML80EL21 / ML90E21 / ML100E21 / ML110EL21 / ML120EL21		EuroCargo Tector 5 ML60E16 / ML65E16 / ML75E16 / ML80EL16 ML75E19 / ML80E19 / ML80EL19 / ML90E19 / ML100E19 / ML110EL19 / ML120EL19 ML75E21 / ML80E21 / ML80EL21 / ML90E21 / ML100E21 / ML110EL21 / ML120EL21	
Year	(09/2019<)		(09/2019<)	
Engine Type	F4AFE411E*N (Euro 6D Temp) F4AFE411F*N (Euro 6D Temp) F4AFE411C*N (Euro 6D Temp)		F4AFE411E*N (Euro 6D Temp) F4AFE411F*N (Euro 6D Temp) F4AFE411C*N (Euro 6D Temp)	
CV(kW) @ rpm	160 (118) @ 2.500 190 (140) @ 2.500 210 (154) @ 2.500		160 (118) @ 2.500 190 (140) @ 2.500 210 (154) @ 2.500	
N. of cylinders/cm3	4 / 4.485		4 / 4.485	
Volts	24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge
				
Compressors type	TM-21 / QP-21		QP-25	
Comments	- TM-21 Clutch 1B Ø150 / 2B Ø149 - Can't be fit in right hand drive vehicles - Fittings not included in the kit - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - Fittings not included in the kit - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox	
Clutch type	Without clutch pulley	With clutch pulley	Without clutch pulley	
	1B Ø150 3.130 rpm	1B Ø150 3.130 rpm	1B Ø150 3.750 rpm	
Kit No.	KC08040128	KC08040128E	KC21090527	
Last update	2020-01-22		2021-09-21	

Vehicle model	EuroCargo Tector 5 ML120E19 / ML140E19 ML120E21 / ML140E21 / ML150E21 / ML160E21		EuroCargo Tector 5 ML120E19 / ML140E19 ML120E21 / ML140E21 / ML150E21 / ML160E21		EuroCargo Tector 5 ML120E19 / ML140E19 ML120E21 / ML140E21 / ML150E21 / ML160E21	
Year	(09/2019<)		(09/2019<)		(09/2019<)	
Engine Type	F4AFE411F*N (Euro 6D Temp) F4AFE411C*N (Euro 6D Temp)		F4AFE411F*N (Euro 6D Temp) F4AFE411C*N (Euro 6D Temp)		F4AFE411F*N (Euro 6D Temp) F4AFE411C*N (Euro 6D Temp)	
CV(kW) @ rpm	190 (140) @ 2.500 210 (154) @ 2.500		190 (140) @ 2.500 210 (154) @ 2.500		190 (140) @ 2.500 210 (154) @ 2.500	
N. of cylinders/cm3	4 / 4.485		4 / 4.485		4 / 4.485	
Volts	24		24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge
						
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM-21 / QP-21		QP-25	
Comments	- Can't be fit in right hand drive vehicles - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - Fittings not included in the kit - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - Fittings not included in the kit - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox	
Clutch type	Without clutch pulley		Without clutch pulley	With clutch pulley	Without clutch pulley	
	2A Ø135 3.520 rpm		1B Ø150 3.130 rpm	1B Ø150 3.130 rpm	1B Ø150 3.750 rpm	
Kit No.	KC07030103		KC08040129	KC08040129E	KC21090528	
Last update	2020-01-22		2020-01-22		2021-09-21	

Vehicle model	EuroCargo Tector 6 CNG ML110EL21 / ML120EL21		EuroCargo Tector 7 ML90E22 / ML100E22 / ML120EL22 / ML120EL25		EuroCargo Tector 7 ML90E22 / ML100E22 / ML120EL22 / ML120EL25		EuroCargo Tector 7 ML120E22 / ML140E22 / ML150E22 / ML160E22 / ML120E25 / ML140E25 ML150E25 / ML160E25 / ML180E25 / ML120E28 / ML140E28 ML150E28 / ML160E28 / ML180E28 / ML150E32 / ML160E32 / ML180E32	
Year	(09/2019>)		(09/2019>)		(09/2019>)		(09/2019<)	
Engine Type	F4GFE601A (Euro VI-D) - CNG		F4AFE611A*N (Euro VI-D) F4AFE611E*N (Euro VI-D)		F4AFE611A*N (Euro VI-D) F4AFE611E*N (Euro VI-D)		F4AFE611A*N (Euro 6D Temp) F4AFE611E*N (Euro 6D Temp) F4AFE611C*N (Euro 6D Temp) F4AFE611D*N (Euro 6D Temp)	
CV(kW) @ rpm	204 (150) @ 2.700		220 (162) @ 2.500 250 (184) @ 2.500		220 (162) @ 2.500 250 (184) @ 2.500		220 (162) @ 2.500 250 (184) @ 2.500 280 (206) @ 2.500 320 (235) @ 2.500	
N. of cylinders/cm3	6 / 5.880		6 / 6.728		6 / 6.728		6 / 6.728	
Volts	24		24		24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge
								
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM13/QP13 - TM15/QP15 - TM16/QP16 UP120/UPF120 - UP150/UPF150 - UP170/UPF 170		TM21/QP21		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15	
Comments	- Can't be fit in right hand drive vehicles - NOT COMPATIBLE with ALLISON automatic gearbox		SD5H14 - SD7H15 - SD5L14 - SD7L15 - Can't be fit in right hand drive vehicles - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox	
Clutch type	Without clutch pulley		Without clutch pulley		With clutch pulley		Without clutch pulley	
	2A Ø135 3.520 rpm		2A Ø135 3.520 rpm				2A Ø135 3.520 rpm	
Kit No.	KC07040111		KC19110495		KC19110496E		KC07040112	
Last update	2020-11-26		2019-12-13		2021-07-09		2020-01-22	

Vehicle model	EuroCargo Tector 7 ML120E22 / ML140E22 / ML150E22 / ML160E22 / ML120E25 / ML140E25 ML150E25 / ML160E25 / ML180E25 / ML120E28 / ML140E28 ML150E28 / ML160E28 / ML180E28 / ML150E32 / ML160E32 / ML180E32		EuroCargo Tector 7 ML120E22 / ML140E22 / ML150E22 / ML160E22 / ML120E25 / ML140E25 ML150E25 / ML160E25 / ML180E25 / ML120E28 / ML140E28 ML150E28 / ML160E28 / ML180E28 / ML150E32 / ML160E32 / ML180E32	
Year	(09/2019<)		(09/2019<)	
Engine Type	F4AFE611A*N (Euro 6D Temp) F4AFE611E*N (Euro 6D Temp) F4AFE611C*N (Euro 6D Temp) F4AFE611D*N (Euro 6D Temp)		F4AFE611A*N (Euro 6D Temp) F4AFE611E*N (Euro 6D Temp) F4AFE611C*N (Euro 6D Temp) F4AFE611D*N (Euro 6D Temp)	
CV(kW) @ rpm	220 (162) @ 2.500 250 (184) @ 2.500 280 (206) @ 2.500 320 (235) @ 2.500		220 (162) @ 2.500 250 (184) @ 2.500 280 (206) @ 2.500 320 (235) @ 2.500	
N. of cylinders/cm3	6 / 6.728		6 / 6.728	
Volts	24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge
				
Compressors type	CS150		TM 21 QP 21	
Comments	- Can't be fit in right hand drive vehicles - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - Fittings not included in the kit - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox	
Clutch type	Without clutch pulley		With clutch pulley	
	8K Ø119 3.487 rpm		1B Ø156 3.012 rpm	
Kit No.	KC23010558		KC13020314E	
Last update	2023-02-24		2020-01-22	

Vehicle model	EuroCargo Tector 5 ML60E16 / ML65E16 / ML75E16 / ML80EL16 ML75E19 / ML80E19 / ML80EL19 / ML90E19 / ML100E19 / ML110EL19 / ML120EL19 ML75E21 / ML80E21 / ML80EL21 / ML90E21 / ML100E21 / ML110EL21 / ML120EL21		EuroCargo Tector 5 ML60E16 / ML65E16 / ML75E16 / ML80EL16 ML75E19 / ML80E19 / ML80EL19 / ML90E19 / ML100E19 / ML110EL19 / ML120EL19 ML75E21 / ML80E21 / ML80EL21 / ML90E21 / ML100E21 / ML110EL21 / ML120EL21	
Year	(2014>09/2019)		(2014>09/2019)	
Engine Type	F4AFE411A*C (Euro 6) F4AFE411B*C (Euro 6) F4AFE411C*C (Euro 6)		F4AFE411A*C (Euro 6) F4AFE411B*C (Euro 6) F4AFE411C*C (Euro 6)	
CV(kW) @ rpm	160 (118) @ 2.500 190 (140) @ 2.500 210 (154) @ 2.500		160 (118) @ 2.500 190 (140) @ 2.500 210 (154) @ 2.500	
N. of cylinders/cm3	4 / 4.485		4 / 4.485	
Volts	24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge
				
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM-21 / QP-21	
Comments	- Can't be fit in right hand drive vehicles - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox		- TM-21 Clutch 1B Ø150 / 2B Ø149 - Can't be fit in right hand drive vehicles - Fittings not included in the kit - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox	
Clutch type	Without clutch pulley		Without clutch pulley	With clutch pulley
	2A Ø135 3.520 rpm		1B Ø150 3.130 rpm	1B Ø150 3.130 rpm
Kit No.	KC07040110		KC08040128	KC08040128E
Last update	2015-04-10		2015-03-23	

Vehicle model	EuroCargo Tector 5 ML120E19 / ML140E19 ML120E21 / ML140E21 / ML150E21 / ML160E21		EuroCargo Tector 5 ML120E19 / ML140E19 ML120E21 / ML140E21 / ML150E21 / ML160E21		EuroCargo Tector 6 CNG ML110EL21 / ML120EL21	EuroCargo Tector 6 CNG ML110EL21 / ML120EL21		
Year	(2014>09/2019)		(2014>09/2019)		(2015>09/2019)	(2015>09/2019)		
Engine Type	F4AFE411B*C (Euro 6) F4AFE411C*C (Euro 6)		F4AFE411B*C (Euro 6) F4AFE411C*C (Euro 6)		F4GFE601A (Euro VI B/C) - CNG	F4GFE601A (Euro VI B/C) - CNG		
CV(kW) @ rpm	190 (140) @ 2.500 210 (154) @ 2.500		190 (140) @ 2.500 210 (154) @ 2.500		204 (150) @ 2.700	204 (150) @ 2.700		
N. of cylinders/cm3	4 / 4.485		4 / 4.485		6 / 5.880	6 / 5.880		
Volts	24		24		24	24		
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	Vehicles with or without A/C		
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge
								
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM-21 / QP-21		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15	TM-21 / QP-21		
Comments	- Can't be fit in right hand drive vehicles - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - Fittings not included in the kit - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - NOT COMPATIBLE with automatic gearbox	- Can't be fit in right hand drive vehicles - NOT COMPATIBLE with automatic gearbox - NOT SUITABLE FOR Euro VI-D vehicles		
Clutch type	Without clutch pulley		Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley		
	2A Ø135 3.520 rpm		1B Ø150 3.130 rpm	1B Ø150 3.130 rpm	2A Ø135 3.520 rpm	1B Ø156 3.012 rpm		
Kit No.	KC07030103		KC08040129	KC08040129E	KC07040111	KC08040130E		
Last update	2015-04-10		2015-03-23		2015-04-10	2015-07-08		

Vehicle model	EuroCargo Tector 6 CNG ML150E21 / ML160E21		EuroCargo Tector 6 CNG ML150E21 / ML160E21		EuroCargo Tector 7 ML80E22 / ML90E22 / ML100E22 / ML110EL22 / ML120EL22		EuroCargo Tector 7 ML80E22 / ML90E22 / ML100E22 / ML110EL22 / ML120EL22	
Year	(2015>09/2019)		(2015>09/2019)		(2014>09/2019)		(2014>09/2019)	
Engine Type	F4GFE601A (Euro VI B/C) - CNG		F4GFE601A (Euro VI B/C) - CNG		F4AFE611A*C (Euro 6)		F4AFE611A*C (Euro 6)	
CV(kW) @ rpm	204 (150) @ 2.700		204 (150) @ 2.700		220 (162) @ 2.500		220 (162) @ 2.500	
N. of cylinders/cm3	6 / 5.880		6 / 5.880		6 / 6.728		6 / 6.728	
Volts	24		24		24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge
								
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM 21 QP 21		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM-21 / QP-21	
Comments	- Can't be fit in right hand drive vehicles - NOT COMPATIBLE with automatic gearbox - NOT SUITABLE FOR Euro VI-D vehicles		- Can't be fit in right hand drive vehicles - NOT COMPATIBLE with automatic gearbox - NOT SUITABLE FOR Euro VI-D vehicles		- Can't be fit in right hand drive vehicles - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox - NOT SUITABLE FOR Euro VI-D vehicles		- Can't be fit in right hand drive vehicles - Fittings not included in the kit - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox - NOT SUITABLE FOR Euro VI-D vehicles	
Clutch type	Without clutch pulley		With clutch pulley		Without clutch pulley		With clutch pulley	
	2A Ø135 3.520 rpm		1B Ø156 3.012 rpm		2A Ø135 3.520 rpm		1B Ø156 3.012 rpm	
Kit No.	KC07040112		KC13020314E		KC07040111		KC08040130E	
Last update	2015-04-13		2015-07-09		2015-04-10		2015-07-08	





Vehicle model	EuroCargo Tector 7 ML120E22 / ML140E22 / ML150E22 / ML160E22 / ML120E25 / ML140E25 ML150E25 / ML160E25 / ML180E25 / ML120E28 / ML140E28 ML150E28 / ML160E28 / ML180E28 / ML150E32 / ML160E32 / ML180E32		EuroCargo Tector 7 ML120E22 / ML140E22 / ML150E22 / ML160E22 / ML120E25 / ML140E25 ML150E25 / ML160E25 / ML180E25 / ML120E28 / ML140E28 ML150E28 / ML160E28 / ML180E28 / ML150E32 / ML160E32 / ML180E32	
Year	(2014>09/2019)		(2014>09/2019)	
Engine Type	F4AFE611A°C (Euro 6) F4AFE611E°C (Euro 6) F4AFE611C°C (Euro 6) F4AFE611D°C (Euro 6)		F4AFE611A°C (Euro 6) F4AFE611E°C (Euro 6) F4AFE611C°C (Euro 6) F4AFE611D°C (Euro 6)	
CV(kW) @ rpm	220 (162) @ 2.500 250 (184) @ 2.500 280 (206) @ 2.500 320 (235) @ 2.500		220 (162) @ 2.500 250 (184) @ 2.500 280 (206) @ 2.500 320 (235) @ 2.500	
N. of cylinders/cm3	6 / 6.728		6 / 6.728	
Volts	24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge
				
Compressors type	CS150		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15	
Comments	- Can't be fit in right hand drive vehicles - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox	
Clutch type	Without clutch pulley		Without clutch pulley	
	8K Ø119 3.487 rpm		2A Ø135 3.520 rpm	
Kit No.	KC23010558		KC07040112	
Last update	2023-02-24		2015-04-13	

Vehicle model	EuroCargo Tector 7 ML120E22 / ML140E22 / ML150E22 / ML160E22 / ML120E25 / ML140E25 ML150E25 / ML160E25 / ML180E25 / ML120E28 / ML140E28 ML150E28 / ML160E28 / ML180E28 / ML150E32 / ML160E32 / ML180E32		EuroCargo Tector 7 4X4 ML110E22 / ML110E25 / ML150E25 / ML150E28	
Year	(2014>09/2019)		(2014>)	
Engine Type	F4AFE611A°C (Euro 6) F4AFE611E°C (Euro 6) F4AFE611C°C (Euro 6) F4AFE611D°C (Euro 6)		F4AFE611A°C (Euro 6) F4AFE611E°C (Euro 6) F4AFE611C°C (Euro 6)	
CV(kW) @ rpm	220 (162) @ 2.500 250 (184) @ 2.500 280 (206) @ 2.500 320 (235) @ 2.500		220 (162) @ 2.500 250 (184) @ 2.500 280 (206) @ 2.500	
N. of cylinders/cm3	6 / 6.728		6 / 6.728	
Volts	24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge
				
Compressors type	TM 21 QP 21		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15	
Comments	- Can't be fit in right hand drive vehicles - Fittings not included in the kit - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox	
Clutch type	With clutch pulley		Without clutch pulley	
	1B Ø156 3.012 rpm		2A Ø135 3.520 rpm	
Kit No.	KC13020314E		KC16110420	
Last update	2015-07-09		2017-03-29	

Vehicle model	EuroCargo Tector 60E14 / 65E14 / 75E14 / 80EL14 60E16 / 65E16 / 75E16 / 80EL16 60E18 / 65E18 / 75E18 / 80E18 / 80EL18 / 90E18 / 100E18 / 110EL18 / 120EL18		EuroCargo Tector 60E14 / 65E14 / 75E14 / 80EL14 60E16 / 65E16 / 75E16 / 80EL16 60E18 / 65E18 / 75E18 / 80E18 / 80EL18 / 90E18 / 100E18 / 110EL18 / 120EL18	
Year	(10/2006)		(10/2006)	
Engine Type	F4AE3481C (Euro 4-5) F4AE3481D (Euro 4-5) F4AE3481B (Euro 4-5)		F4AE3481C (Euro 4-5) F4AE3481D (Euro 4-5) F4AE3481B (Euro 4-5)	
CV(kW) @ rpm	140 (103) @ 2.700 160 (118) @ 2.700 180 (132) @ 2.700		140 (103) @ 2.700 160 (118) @ 2.700 180 (132) @ 2.700	
N. of cylinders/cm3	4 / 3.920		4 / 3.920	
Volts	24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge
				
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM-21 / QP-21	
Comments	- Can't be fit in right hand drive vehicles. - NOT COMPATIBLE with ALLISON automatic gearbox		- TM-21 Clutch 1B Ø150 / 2B Ø149 - Can't be fit in right hand drive vehicles - Fittings not included in the kit - NOT COMPATIBLE with ALLISON automatic gearbox	
Clutch type	Without clutch pulley		Without clutch pulley	With clutch pulley
	2A Ø135 3.800 rpm		1B Ø150 3.130 rpm	1B Ø150 3.130 rpm
Kit No.	KC07040110		KC08040128	KC08040128E
Last update	2013-12-18		2014-06-30	

Vehicle model	EuroCargo Tector 120E18 / 130E18 / 140E18 150E18 / 160E18		EuroCargo Tector 120E18 / 130E18 / 140E18 150E18 / 160E18		EuroCargo Tector 80E22 / 90E22 / 100E22 / 110EL22 / 120EL22		EuroCargo Tector 80E22 / 90E22 / 100E22 / 110EL22 / 120EL22		EuroCargo Tector 110EL20 CNG / 120EL20 CNG		EuroCargo Tector 110EL20 CNG / 120EL20 CNG	
Year	(06/2006>)		(06/2006>)		(10/2006>)		(10/2006>)		(01/2011>)		(01/2011>)	
Engine Type	F4AE3481A (Euro 4-5)		F4AE3481A (Euro 4-5)		F4AE3681B-P (Euro4-5)		F4AE3681B-P (Euro4-5)		FPT Tector 6 CNG engine		FPT Tector 6 CNG engine	
CV(kW) @ rpm	182 (134) @ 2.700		182 (134) @ 2.700		217 (159) @ 2.700		217 (159) @ 2.700		200 (147) @ 2.700		200 (147) @ 2.700	
N. of cylinders/cm3	4 / 3.920		4 / 3.920		6 / 5.880		6 / 5.880		6 / 5.880		6 / 5.880	
Volts	24		24		24		24		24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM-21 / QP-21		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM-21 / QP-21		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM-21 / QP-21	
Comments	- Can't be fit in right hand drive vehicles. - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - Fittings not included in the kit - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles. - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - Fittings not included in the kit - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles. - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - Fittings not included in the kit - NOT COMPATIBLE with ALLISON automatic gearbox	
Clutch type	Without clutch pulley		Without clutch pulley		Without clutch pulley		With clutch pulley		Without clutch pulley		With clutch pulley	
	2A Ø135 3.800 rpm		1B Ø150 3.130 rpm		2A Ø135 3.800 rpm		1B Ø156 3.012 rpm		2A Ø135 3.800 rpm		1B Ø156 3.012 rpm	
Kit No.	KC07030103		KC08040129	KC08040129E	KC07040111		KC08040130E		KC07040111		KC08040130E	
Last update	2013-12-18		2014-06-30		2013-12-18		2014-06-30		2013-12-18		2014-06-30	

Vehicle model	EuroCargo Tector 120E22 / 130E22 / 140E22 / 150E22 / 160E22 / 120E25 / 130E25 / 140E25 / 150E25 160E25 / 180E25 / 190EL25 / 120E28 / 130E28 / 140E28 / 150E28 / 160E28 / 180E28 190EL28 / 150E30 / 160E30 / 180E30 / 190EL30		EuroCargo Tector 120E22 / 130E22 / 140E22 / 150E22 / 160E22 / 120E25 / 130E25 / 140E25 / 150E25 160E25 / 180E25 / 190EL25 / 120E28 / 130E28 / 140E28 / 150E28 / 160E28 / 180E28 190EL28 / 150E30 / 160E30 / 180E30 / 190EL30	
Year	(10/2006>)		(10/2006>)	
Engine Type	F4AE3681B-P (Euro 4-5)// F4AE3681D-P (Euro 4-5) F4AE3681E-P (Euro 4-5)//F4AE3681A-P (Euro 4-5)		F4AE3681B-P (Euro 4-5)// F4AE3681D-P (Euro 4-5) F4AE3681E-P (Euro 4-5)//F4AE3681A-P (Euro 4-5)	
CV(kW) @ rpm	217 (159) / 251 (184) @ 2.700 279 (205) / 299 (220) @ 2.500		217 (159) / 251 (184) @ 2.700 279 (205) / 299 (220) @ 2.500	
N. of cylinders/cm3	6 / 5.880		6 / 5.880	
Volts	24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge
				
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		CS150	
Comments	- Can't be fit in right hand drive vehicles. - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles. - NOT COMPATIBLE with ALLISON automatic gearbox	
Clutch type	Without clutch pulley		Without clutch pulley	
	2A Ø135 3.800 rpm		8K Ø119 3.487 rpm	
Kit No.	KC07040112		KC23010558	
Last update	2013-12-18		2023-02-24	

Vehicle model	EuroCargo Tector 120E22 / 130E22 / 140E22 / 150E22 / 160E22 / 120E25 / 130E25 / 140E25 / 150E25 160E25 / 180E25 / 190EL25 / 120E28 / 130E28 / 140E28 / 150E28 / 160E28 / 180E28 190EL28 / 150E30 / 160E30 / 180E30 / 190EL30		EuroCargo Tector 150E20 CNG / 160E20 CNG		EuroCargo Tector 150E20 CNG / 160E20 CNG		EuroCargo Tector 4X4 110E22 / 110E25 / 150E25 / 150E28	
Year	(10/2006>)		(01/2011>)		(01/2011>)		(10/2006>)	
Engine Type	F4AE3681B-P (Euro 4-5)// F4AE3681D-P (Euro 4-5) F4AE3681E-P (Euro 4-5)//F4AE3681A-P (Euro 4-5)		FPT Tector 6 CNG engine		FPT Tector 6 CNG engine		F4AE3681B-P (Euro 4-5)// F4AE3681D-P (Euro 4-5) F4AE3681E-P (Euro 4-5)//F4AE3681A-P (Euro 4-5)	
CV(kW) @ rpm	217 (159) / 251 (184) @ 2.700 279 (205) / 299 (220) @ 2.500		200 (147) @ 2.700		200 (147) @ 2.500		217 (159) / 251 (184) @ 2.700 279 (205) / 299 (220) @ 2.500	
N. of cylinders/cm3	6 / 5.880		6 / 5.880		6 / 5.880		6 / 5.880	
Volts	24		24		24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge
								
Compressors type	TM 21 QP 21		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM 21 QP 21		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15	
Comments	- Can't be fit in right hand drive vehicles - Fittings not included in the kit - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles. - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - Fittings not included in the kit - NOT COMPATIBLE with ALLISON automatic gearbox		- Can't be fit in right hand drive vehicles - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox	
Clutch type	With clutch pulley		Without clutch pulley		With clutch pulley		Without clutch pulley	
	1B Ø156 3.012 rpm		2A Ø135 3.800 rpm		1B Ø156 3.012 rpm		2A Ø135 3.520 rpm	
Kit No.	KC13020314E		KC07040112		KC13020314E		KC16110420	
Last update	2015-07-09		2013-12-18		2015-07-09		2017-03-29	

Vehicle model	EuroCargo Tector 60E13 / 65E13 / 75E13 60E15 / 65E15 / 75E15 / 80EL15 75E17 / 80E17 / 90E17 / 100E17 / 80EL17 / 100EL17 / 120EL17		EuroCargo Tector 75E18 / 80E18 / 90E18 / 100E18 80E21 / 90E21 / 100E21 / 110EL21 / 120EL21	
Year	(10/2002>)		(2001>)	
Engine Type	F4AE0481D (Euro 3) F4AE0481C (Euro 3) F4AE0481A (Euro 3)		F4AE0681E (Euro 3) F4AE0681D (Euro 3)	
CV(kW) @ rpm	129 (95) @ 2.700 150 (110) @ 2.700 170 (125) @ 2.700		182 (134) @ 2.700 209 (154) @ 2.700	
N. of cylinders/cm3	4 / 3.920		6 / 5.880	
Volts	24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge
				
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15	
Comments	- From chassis number ZCFA75CO102391603 (truck number 3298466). - Can't be fit in right hand drive vehicles.		- Can't be fit in right hand drive vehicles.	
Clutch type	Without clutch pulley		Without clutch pulley	
	2A Ø135 3.800 rpm		2A Ø135 3.800 rpm	
Kit No.	KC05100016		KC05100017	
Last update	2013-12-18		2013-12-18	

Vehicle model	EuroCargo Tector 120E18 / 130E18 / 140E18 / 150E18 / 120E21 / 130E21 / 140E21 / 150E21 160E21 / 180E21 / 120E24 / 130E24 / 140E24 / 150E24 / 160E24 180E24 / 120E28 / 130E28 / 140E28 / 150E28 / 160E28 / 180E28		S-WAY 190S31 / 260S31 / 190S33 / 260S33 190S36 / 260S36		S-WAY 190S31 / 260S31 / 190S33 / 260S33 190S36 / 260S36		STRALIS 190S31 / 260S31 / 190S33 / 260S33 190S36 / 260S36	
Year	(2001>)		(01/2022>)		(01/2022>)		(01/2016>)	
Engine Type	F4AE0681E (Euro 3) F4AE0681B (Euro 3) F4AE0681A (Euro 3)		Cursor 9 (Euro 6) F2CFE611D F2CFE611C F2CFE611B		Cursor 9 (Euro 6) F2CFE611D F2CFE611C F2CFE611B		Cursor 9 (Euro 6) F2CFE611D F2CFE611C F2CFE611B	
CV(kW) @ rpm	182 (134) @ 2.700 240 (176) @ 2.700 275 (202) @ 2.500		340 (250) @ 2.400 360 (265) @ 2.400 400 (294) @ 2.400		340 (250) @ 2.200 360 (265) @ 2.200 400 (294) @ 2.200		310 (228) @ 2.400 330 (243) @ 2.400 360 (265) @ 2.400	
N. of cylinders/cm3	6 / 5.880		6 / 8.709		6 / 8.709		6 / 8.709	
Volts	24		24		24		24	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge
								
Compressors type	TM 13 / 15 / 16 QP 13 / 15 / 16 UP-UPF 120 / 150 / 170 SD5H14 / SD7H15 / SD5L14 / SD7L15		TM 21 QP 21		QP 25		TM 21 QP 21	
Comments	- Can't be fit in right hand drive vehicles.		- Can be fit in right hand drive vehicles. - Fittings not included in the kit - Not suitable for vehicles equipped with front pneumatic suspension		- Can be fit in right hand drive vehicles. - Fittings not included in the kit - Not suitable for vehicles equipped with front pneumatic suspension		- Can be fit in right hand drive vehicles. - Fittings not included in the kit - Not suitable for vehicles equipped with front pneumatic suspension - Only suitable for vehicles after january 2016	
Clutch type	Without clutch pulley		Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley
	2A Ø135 3.800 rpm		Poly-V 8K Ø137 3.260 rpm	Poly-V 8K Ø137 3.260 rpm	Poly-V 8K Ø137 3.680 rpm	Poly-V 8K Ø137 3.680 rpm	Poly-V 8K Ø137 3.260 rpm	Poly-V 8K Ø137 3.260 rpm
Kit No.	KC05100018		KC23010561	KC23010561E	KC23040571	KC23040571E	KC15060393	KC15060393E
Last update	2013-12-18		2024-02-06		2024-02-06		2016-07-19	



Vehicle model	STRALIS 190S31 / 260S31 190S33 / 260S33 190S36 / 260S36					
Year	(2004>)					
Engine Type	Cursor 8 (Euro 5 / EEV) F2B E3681C F2B E3681B F2B E3681A					
CV(kW) @ rpm	310 (228) @ 2.400 330 (243) @ 2.400 360 (265) @ 2.400					
N. of cylinders/cm3	6 / 7.790					
Volts	24					
Air Conditioning	Vehicles with or without A/C					
Recommended fittings	Suction	Discharge				
						
Compressors type	TM 21 QP 21					
Comments	- Can be fit in right hand drive vehicles. - Fittings not included in the kit - Not suitable for vehicles equipped with front pneumatic suspension					
Clutch type	Without clutch pulley	With clutch pulley				
	Poly-V 8K Ø137 3.258 rpm	Poly-V 8K Ø137 3.258 rpm				
Kit No.	KC11050229	KC11050229E				
Last update	2014-08-01					