

Vehicle model	DAILY 2.3 35 / S12-C12 35 / S14-C14 35-40-50 / S16-C16	DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - <b>CNG</b>	DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - <b>CNG</b>			
Year	(09/2019>)	(09/2021>)	(09/2021>)			
Engine Type	F1AGL411 (Euro 6d-full / Euro VI-E)	F1CFL (Euro 6d-full / Euro VI-E) <b>F1CFA401C (CNG)</b>	F1CFL (Euro 6d-full / Euro VI-E) <b>F1CFA401C (CNG)</b>			
CV(kW) @ rpm	116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600	160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500	160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500			
N. of cylinders/cm3	4 / 2.287	4 / 2.998	4 / 2.998			
Volts	12	12	12			
Air Conditioning	Vehicles with or without A/C	Vehicles with or without A/C	Vehicles with or without A/C			
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge
Compressors type		25cc: 236F5H25D10 IPH	16cc: 1197161000 SALAMI 16,6cc			
Comments	<ul style="list-style-type: none"> <li>- KIT SUITABLE FOR OVERSIZED OIL SUMP IVECO OPTION. Ref. 72617 (SB20100050)</li> <li>- Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic.</li> <li>- Can be fit on AWD vehicles</li> <li>- Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 3.0l engine</li> <li>- Not included in the kit: <ul style="list-style-type: none"> <li>* Pump clutch P/N 1112007022</li> <li>* Hydraulic pump 16,6cc (For other displacement consult) P/N 1197161000</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>- Can be fit in right hand drive vehicles</li> <li>- Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398</li> <li>- Can be fit on AWD vehicles</li> <li>- It is required to purchase the fan channeler IVECO ref. 5802725496.</li> <li>- Mandatory increase of engine idle speed to 1150 rpm. Operation to be done in an official Iveco Dealer.</li> <li>- IPH hydraulic pump neither included in the kit nor available in Oliva Torras catalogue</li> </ul>	<ul style="list-style-type: none"> <li>- Can be fit in right hand drive vehicles</li> <li>- Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398</li> <li>- Can be fit on AWD vehicles</li> <li>- Not included in the kit: <ul style="list-style-type: none"> <li>* Pump clutch P/N 1112007022</li> <li>* Hydraulic pump 16,6cc (For other displacement consult) P/N 1197161000</li> </ul> </li> </ul>			
Clutch type	Without clutch pulley	Without clutch pulley	Without clutch pulley			
		Poly-V 8K Ø133 932 rpm	Poly-V 8K Ø134 925 rpm			
Kit No.	KH19107015	KH15017003	KH20017017			
Last update	2024-02-19	2021-12-14	2021-12-15			

Vehicle model	DAILY 2.3 35 / S12-C12 35 / S14-C14 35-40-50 / S16-C16	DAILY 3.0  35S16 / 35C16 / 50C16 / 60C16 / 65C16 / 70C16 35S18 / 35C18 / 50C18 / 60C18 / 65C18 / 70C18 35S14 / 35C14 / 50C14 / 60C14 / 65C14 / 70C14 - <b>CNG / NPW</b>		DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - <b>CNG</b>
Year	(09/2019>)	(09/2019>)		(09/2019>)
Engine Type	F1AGL411X (Euro 6d-temp) F1AGL411Y (Euro 6d-temp) F1AGL411W (Euro 6d-temp) F1AGL411U (Euro 6d-temp)	F1CFL4116 (Euro 6d-temp) F1CFL4117 (Euro 6d-temp) <b>F1CFA401C (CNG)</b>		F1CFL4116 (Euro 6d-temp) F1CFL4117 (Euro 6d-temp) F1CFL4115 (Euro 6d-temp) <b>F1CFA401C (CNG)</b>
CV(kW) @ rpm	116 (85) @ 3.600 136 (100) @ 3.600 156 (115) @ 3.600	160 (118) @ 3.500 180 (132) @ 3.500 136 (100) @ 3.500		160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500
N. of cylinders/cm3	4 / 2.287	4 / 2.998		4 / 2.998
Volts	12	12		12
Air Conditioning	Vehicles with or without A/C	Vehicles with or without A/C		Vehicles with or without A/C
Recommended fittings	Suction	Discharge	Suction	Discharge
Compressors type		25cc: 236F5H25D10 IPH		16cc: 1197161000 SALAMI 16,6cc
Comments	- KIT SUITABLE FOR OVERSIZED OIL SUMP IVECO OPTION. Ref. 72617 (SB20100050) - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. - Can be fit on AWD vehicles - Model 35S16 / 35C16 / 40C16 / 50C16 can also be equipped with the 3.0l engine - Not included in the kit: * Pump clutch P/N 1112007022 * Hydraulic pump 16,6cc (For other displacement consult) P/N 1197161000	- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - It is required to purchase the fan channeler IVECO ref. 5802725496. - Mandatory increase of engine idle speed to 1150 rpm. Operation to be done in an official Iveco Dealer. - IPH hydraulic pump neither included in the kit nor available in Oliva Torras catalogue		- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Not included in the kit: * Pump clutch P/N 1112007022 * Hydraulic pump 16,6cc (For other displacement consult) P/N 1197161000
Clutch type	Without clutch pulley	Without clutch pulley		Without clutch pulley
		Poly-V 8K Ø133 932 rpm		Poly-V 8K Ø134 925 rpm
Kit No.	KH19107015	KH15017003		KH20017017
Last update	2024-02-19	2021-09-23		2020-03-02

<b>Vehicle model</b>	DAILY 3.0 35S15 / 35C15 / 40C15 / 45C15 / 50C15 / 60C15 / 65C15 / 70C15 / 72C15 35S18 / 35C18 / 40C18 / 45C18 / 50C18 / 60C18 / 65C18 / 70C18 / 72C18 35S14 / 35C14 / 40C14 / 50C14 / 60C14 / 65C14 / 70C14 / 72C14 - <b>CNG / NPW</b>	DAILY 3.0 35S15 / 35C15 / 40C15 / 45C15 / 50C15 / 60C15 / 65C15 / 70C15 / 72C15 35S18 / 35C18 / 40C18 / 45C18 / 50C18 / 60C18 / 65C18 / 70C18 / 72C18 35S14 / 35C14 / 40C14 / 50C14 / 60C14 / 65C14 / 70C14 / 72C14 - <b>CNG / NPW</b>
<b>Year</b>	(09/2014>)	(09/2014>)
<b>Engine Type</b>	F1CFL411E*A / F1CGL411E*A / F1CGL411A*E (Euro 6) F1CFL411F*A / F1CGL411F*A / F1CGL411B*E (Euro 6) <b>F1CFA401A*A (CNG)</b>	F1CFL411E*A / F1CGL411E*A / F1CGL411A*E (Euro 6) F1CFL411F*A / F1CGL411F*A / F1CGL411B*E (Euro 6) <b>F1CFA401A*A (CNG)</b>
<b>CV(kW) @ rpm</b>	150 (110) @ 800 180 (132) @ 800 136 (100) @ 800 (methanol supply)	150 (110) @ 800 180 (132) @ 800 136 (100) @ 800 (methanol supply)
<b>N. of cylinders/cm3</b>	4 / 2.998	4 / 2.998
<b>Volts</b>	12	12
<b>Air Conditioning</b>	Vehicles with or without A/C	Vehicles with or without A/C
<b>Recommended fittings</b>	Suction Discharge	Suction Discharge
<b>Compressors type</b>	25cc: 236F5H25D10 IPH	16cc: 1197161000 SALAMI 16,6cc
<b>Comments</b>	<ul style="list-style-type: none"> <li>- Can be fit in right hand drive vehicles</li> <li>- Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398</li> <li>- Can be fit on AWD vehicles</li> <li>- It is required to purchase the fan channeler IVECO ref. 5802725496.</li> <li>- Mandatory increase of engine idle speed to 1150 rpm. Operation to be done in an official Iveco Dealer.</li> <li>- IPH hydraulic pump neither included in the kit nor available in Oliva Torras catalogue</li> </ul>	<ul style="list-style-type: none"> <li>- Can be fit in right hand drive vehicles</li> <li>- Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398</li> <li>- Can be fit on AWD vehicles</li> <li>- Not included in the kit: <ul style="list-style-type: none"> <li>* Pump clutch P/N 1112007022</li> <li>* Hydraulic pump 16,6cc (For other displacement consult) P/N 1197161000</li> </ul> </li> </ul>
<b>Clutch type</b>	Without clutch pulley Poly-V 8K Ø133 932 rpm	Without clutch pulley Poly-V 8K Ø134 925 rpm
<b>Kit No.</b>	KH15017003	KH20017017
<b>Last update</b>	2021-09-23	2023-02-06

<b>Vehicle model</b>	<p>DAILY 2.3</p> <p>33S11 / 35S11 / 35C11</p> <p>33S13 / 35S13 / 35C13</p> <p>33S15 / 35S15 / 35C15</p>		<p>DAILY 3.0</p> <p>35S15 / 35C15 / 50C15 / 65C15 / 70C15</p> <p>35S17 / 35C17 / 50C17 / 65C17 / 70C17</p>			
<b>Year</b>	(08/2014>)		(09/2014>)			
<b>Engine Type</b>	<p>F1AFL411A*A (Euro 5b+)</p> <p>F1AFL411B*A (Euro 5b+)</p> <p>F1AFL411C*A (Euro 5b+)</p>		<p>F1CFL411J*C (Euro 5b+)</p> <p>F1CFL411H*C (Euro 5b+)</p>			
<b>CV(kW) @ rpm</b>	<p>106 (78) @ 3.900</p> <p>126 (93) / 146 (107) @ 3.600</p>		<p>146 (107) @ 3.500</p> <p>170 (125) @ 3.500</p>			
<b>N. of cylinders/cm3</b>	4 / 2.287		4 / 2.998			
<b>Volts</b>	12		12			
<b>Air Conditioning</b>	Vehicles with or without A/C		Vehicles with or without A/C			
<b>Recommended fittings</b>	Suction	Discharge	Suction	Discharge		
<b>Compressors type</b>			25cc: 236F5H25D10 IPH			
<b>Comments</b>	<p>- Model 35S15 / 35C15 can also be equipped with the 3.0l engineç</p> <p>- Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic.</p> <p>- Not included in the kit:</p> <ul style="list-style-type: none"> <li>* Pump clutch P/N 1112007022</li> <li>* Hydraulic pump 16,6cc (For other displacement consult) P/N 1197161000</li> </ul>		<p>- Can be fit in right hand drive vehicles</p> <p>- Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398</p> <p>- Can be fit on AWD vehicles</p> <p>- It is required to purchase the fan channeler IVECO ref. 5802725496.</p> <p>- Mandatory increase of engine idle speed to 1150 rpm. Operation to be done in an official Iveco Dealer.</p> <p>- IPH hydraulic pump neither included in the kit nor available in Oliva Torras catalogue</p>			
<b>Clutch type</b>	Without clutch pulley		Without clutch pulley			
			<p>Poly-V 8K Ø133</p> <p>932 rpm</p>			
<b>Kit No.</b>	KH19107015		KH15017003			
<b>Last update</b>	2024-02-19		2021-09-23			