

Vehicle model	DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG		DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG	
Year	(09/2021>)		(09/2021>)	
Engine Type	F1CFL (Euro 6d-full / Euro VI-E) F1CFA401C (CNG)		F1CFL (Euro 6d-full / Euro VI-E) F1CFA401C (CNG)	
CV(kW) @ rpm	160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500		160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500	
N. of cylinders/cm3	4 / 2.998		4 / 2.998	
Volts	12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction		Discharge	
Compressors type	25cc: 236F5H25D10 IPH		16cc: 1197161000 SALAMI 16,6cc	
Comments	<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - It is required to purchase the fan channeler IVECO ref. 5802725496. - Mandatory increase of engine idle speed to 1150 rpm. Operation to be done in an official Iveco Dealer. - IPH hydraulic pump neither included in the kit nor available in Oliva Torras catalogue 		<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Not included in the kit: <ul style="list-style-type: none"> * Pump clutch P/N 1112007022 * Hydraulic pump 16,6cc (For other displacement consult) P/N 1197161000 	
Clutch type	Without clutch pulley		Without clutch pulley	
	Poly-V 8K Ø133 932 rpm		Poly-V 8K Ø134 925 rpm	
Kit No.	KH15017003		KH20017017	
Last update	2021-12-14		2021-12-15	

Vehicle model	DAILY 3.0 35S16 / 35C16 / 50C16 / 60C16 / 65C16 / 70C16 35S18 / 35C18 / 50C18 / 60C18 / 65C18 / 70C18 35S14 / 35C14 / 50C14 / 60C14 / 65C14 / 70C14 - CNG / NPW		DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG	
Year	(09/2019>)		(09/2019>)	
Engine Type	F1CFL4116 (Euro 6d-temp) F1CFL4117 (Euro 6d-temp) F1CFA401C (CNG)		F1CFL4116 (Euro 6d-temp) F1CFL4117 (Euro 6d-temp) F1CFL4115 (Euro 6d-temp) F1CFA401C (CNG)	
CV(kW) @ rpm	160 (118) @ 3.500 180 (132) @ 3.500 136 (100) @ 3.500		160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500	
N. of cylinders/cm3	4 / 2.998		4 / 2.998	
Volts	12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge
Compressors type	25cc: 236F5H25D10 IPH		16cc: 1197161000 SALAMI 16,6cc	
Comments	<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - It is required to purchase the fan channeler IVECO ref. 5802725496. - Mandatory increase of engine idle speed to 1150 rpm. Operation to be done in an official Iveco Dealer. - IPH hydraulic pump neither included in the kit nor available in Oliva Torras catalogue 		<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Not included in the kit: <ul style="list-style-type: none"> * Pump clutch P/N 1112007022 * Hydraulic pump 16,6cc (For other displacement consult) P/N 1197161000 	
Clutch type	Without clutch pulley		Without clutch pulley	
	Poly-V 8K Ø133 932 rpm		Poly-V 8K Ø134 925 rpm	
Kit No.	KH15017003		KH20017017	
Last update	2021-09-23		2020-03-02	

Vehicle model	DAILY 3.0 35S15 / 35C15 / 40C15 / 45C15 / 50C15 / 60C15 / 65C15 / 70C15 / 72C15 35S18 / 35C18 / 40C18 / 45C18 / 50C18 / 60C18 / 65C18 / 70C18 / 72C18 35S14 / 35C14 / 40C14 / 50C14 / 60C14 / 65C14 / 70C14 / 72C14 - CNG / NPW	DAILY 3.0 35S15 / 35C15 / 40C15 / 45C15 / 50C15 / 60C15 / 65C15 / 70C15 / 72C15 35S18 / 35C18 / 40C18 / 45C18 / 50C18 / 60C18 / 65C18 / 70C18 / 72C18 35S14 / 35C14 / 40C14 / 50C14 / 60C14 / 65C14 / 70C14 / 72C14 - CNG / NPW
Year	(09/2014>)	(09/2014>)
Engine Type	F1CFL411E*A / F1CGL411E*A / F1CGL411A*E (Euro 6) F1CFL411F*A / F1CGL411F*A / F1CGL411B*E (Euro 6) F1CFA401A*A (CNG)	F1CFL411E*A / F1CGL411E*A / F1CGL411A*E (Euro 6) F1CFL411F*A / F1CGL411F*A / F1CGL411B*E (Euro 6) F1CFA401A*A (CNG)
CV(kW) @ rpm	150 (110) @ 800 180 (132) @ 800 136 (100) @ 800 (methanol supply)	150 (110) @ 800 180 (132) @ 800 136 (100) @ 800 (methanol supply)
N. of cylinders/cm3	4 / 2.998	4 / 2.998
Volts	12	12
Air Conditioning	Vehicles with or without A/C	Vehicles with or without A/C
Recommended fittings	Suction Discharge	Suction Discharge
Compressors type	25cc: 236F5H25D10 IPH	16cc: 1197161000 SALAMI 16,6cc
Comments	<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - It is required to purchase the fan channeler IVECO ref. 5802725496. - Mandatory increase of engine idle speed to 1150 rpm. Operation to be done in an official Iveco Dealer. - IPH hydraulic pump neither included in the kit nor available in Oliva Torras catalogue 	<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - Not included in the kit: <ul style="list-style-type: none"> * Pump clutch P/N 1112007022 * Hydraulic pump 16,6cc (For other displacement consult) P/N 1197161000
Clutch type	Without clutch pulley Poly-V 8K Ø133 932 rpm	Without clutch pulley Poly-V 8K Ø134 925 rpm
Kit No.	KH15017003	KH20017017
Last update	2021-09-23	2023-02-06

Vehicle model	DAILY 3.0 35S15 / 35C15 / 50C15 / 65C15 / 70C15 35S17 / 35C17 / 50C17 / 65C17 / 70C17				
Year	(09/2014>)				
Engine Type	F1CFL411J*C (Euro 5b+) F1CFL411H*C (Euro 5b+)				
CV(kW) @ rpm	146 (107) @ 3.500 170 (125) @ 3.500				
N. of cylinders/cm3	4 / 2.998				
Volts	12				
Air Conditioning	Vehicles with or without A/C				
Recommended fittings	Suction	Discharge			
Compressors type	25cc: 236F5H25D10 IPH				
Comments	<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 - Can be fit on AWD vehicles - It is required to purchase the fan channeller IVECO ref. 5802725496. - Mandatory increase of engine idle speed to 1150 rpm. Operation to be done in an official Iveco Dealer. - IPH hydraulic pump neither included in the kit nor available in Oliva Torras catalogue 				
Clutch type	Without clutch pulley				
	Poly-V 8K Ø133 932 rpm				
Kit No.	KH15017003				
Last update	2021-09-23				